

9120 Centerlinks Commerce Dr - Ste 3 • Fort Myers • FL • 33912 • USA • Phone: 239-461-5522 • Fax: 239-337-7887

MONDAY - FRIDAY 8:00AM - 8:00PM (US EASTERN TIME)

Lifetime'

Tech Support

24 Month*

Product Warranty

Worldwide*_₩

Shipping

Lowest Price*

Guarantee


www.solarilluminations.com • sales@solarilluminations.com

No Hassle* Returns









SL40

SL40 Solar 60W/80W/100W (Supplied Without Pole)

LUMINAIRE

- Three user/installer selectable operational mode choices.
- Timed mode Offers automatic illumination at dusk at 100%, 70%, or 50% output
- Motion sensor mode Offers automatic illumination at dusk upon motion detection at either 100%, 70%, or 50% output
- Mixed mode Offers automatic illumination at dusk for up to 6 hours at 100%, 70%, or 50% output, then off, except upon motion detection until dawn at 100%, 70%, or 50% output
- Select the desired lighting mode and/or output using the included remote control
- 60 Watt emits 6,500 lumens
- 80 Watt emits 8,500 lumens
- 100 Watt emits 10,500 lumens
- 5,500~6,000k LED color temperature
- Aluminum construction
- IP65 weather rating
- 60 Watt Dimensions approx. 38" x 14" x 4" (96cm x 35cm x 10cm)
- 80 Watt Dimensions aprox. 44" x 14" x 4" (112cm x 35cm x 10cm)
- 100 Watt Dimensions approx. 50" x 14" x 4" (127cm x 35cm x 10cm)
- Gray / aluminum finish

SOLAR PANEL

- 60 Watt version is fitted with a 18V 64 Watt solar panel
- 80 Watt version is fitted with a 18V 85 Watt solar panel
- 100 Watt version is fitted with a 18V 102 Watt solar panel
- Glass covered solar panel is integrated into the top of the fixture

BATTERY

- Lithium battery pack included and pre-installed
- 60 Watt supplied with 12.8 V 302 Watt-hour battery
- 80 Watt supplied with 12.8V 403 Watt-hour battery
- 100 Watt supplied with 12.8V 502 Watt-hour battery
- The long life battery is replaceable when required

Worldwide*

Lowest Price*
Guarantee

Lifetime*
Tech Support

24 Month*
Product Warranty

No Hassle*

9120 Centerlinks Commerce Dr - Ste 3 • Fort Myers • FL • 33912 • USA • Phone: 239-461-5522 • Fax: 239-337-7887


MONDAY - FRIDAY 8:00AM - 8:00PM (US EASTERN TIME)

www.solarilluminations.com • sales@solarilluminations.com

DAT696/0424







SL40

SL4 Solar 60W/80W/100W (Supplied Without Pole)

POLE

- Pole is not included. See product code SL41 if pole is required.
- Light fixture will mount to the top of a 3" diameter pole.
- An optional tenon/adaptor is required for other pole diameters
- Fixture can be mounted to a 3" diameter support arm
- Maximum recommended mounting height for the fixture is as follows:
- 60 Watt Up to aprox. 26' (8M)
- 80 Watt Up to aprox. 29' (9M)
- 100 Watt Up to aprox. 33' (10M)

CHARGE CONTROL

- Internal battery over-charge and dis-charge protection
- · Automatic light activation at sunset



Remote included to select desired operational mode modemomode.

Worldwide*

Lowest Price*
Guarantee

Lifetime*
Tech Support

24 Month*
Product Warranty

No Hassle*

9120 Centerlinks Commerce Dr - Ste 3 • Fort Myers • FL • 33912 • USA • Phone: 239-461-5522 • Fax: 239-337-7887

MONDAY - FRIDAY 8:00AM - 8:00PM (US EASTERN TIME)

www.solarilluminations.com • sales@solarilluminations.com