



# FL61

## Solar Mini LED Flood Light System

### TECHNICAL SPECIFICATIONS

Manufactured in an ISO9001:2008 'Quality Assured' facility.

#### GENERAL

- This system is typically offers dusk till dawn lighting.
- User programmable illumination time (dusk to dawn or for example dusk for 6 hours, dusk for 7 hours, dusk for 8 hours etc).
- One light fixture is included in this system.
- The fixture is fitted with powerful 10w SMD/LED.
- Total 800-950 Lumens per lamp (subject to color temperature).
- LED beam angle is approx. 120 degrees.
- Choice of white, warm white or RGB (multi-color LED)
- White LED color temperature is approx. 6000-6500k.
- Warm white LED color temperature is approx. 3000-3500k.
- RGB LED provides 16 different colors, dimmable feature and color changing option.
- RGB model comes complete with a IR remote control.
- The light fixture is fitted with approximately 18' of pre-wired cable which is pre-plugged ready for easy connection to the battery box. Additional extension cable is available (upon request) as an option.
- All connections are simply plug & play.
- The light fixture is weather rated to I.P 65, and is fitted with a U shape mounting bracket.
- The fixture mounting bracket has pre-drilled holes to allow fixing using screws or bolts (not included).
- Gray colored finish of light fixture.
- Light fixture dimensions approx. 4.5" x 3.5" x 3" (11cm x 9cm x 8cm) LxWxD.
- Up to 3 days of autonomy (subject to time length of night time illumination and other factors).

#### BATTERY BOX

- A plastic weatherproof battery box is supplied to accommodate the battery.
- One high capacity 12 Volt 18 Amp/Hr sealed lead acid battery is supplied.
- Battery type is AGM. Gel battery is available by special order.
- The battery box also houses the PCB controller.
- This system includes a programmable control module and regulates and manages the solar panel power, battery power and illumination timer.
- The compact control module has LED indicators to display status, input connections for solar panel and batteries and output connections for the lamp.
- User or installer can set the control module to run from dusk and then shut off after a certain amount of hours.
- The battery box is approx. 10.5" x 8" x 4.5" (27cm x 20cm x 12cm) LxWxD.

#### SOLAR PANEL

- High quality, aluminum framed, powerful 40 watt solar panel is included and is fitted with approximately 10' of cable/cord. Additional cord is available as an optional extra.
- The solar panel cord connects directly to the battery box.
- The solar panel support is supplied with a fold-out 'U' shape bracket which can be used to mount it to a suitable surface.
- The 40w solar panel dimensions approx. 33" x 20" x 1.5" (84cm x 51cm x 4cm) LxWxD.



**One Year\***  
Warranty

**Low Price**  
Guarantee

**No Hassle\***  
Returns

**Worldwide**  
Shipping

**Lifetime**  
Tech Support

5611 Halifax Avenue • Fort Myers • FL • 33912 • USA • Phone: 239-461-5522 • Fax: 239-337-7887

MONDAY - FRIDAY 10.00AM - 4.00PM (US EASTERN TIME)

www.solarilluminations.com • sales@solarilluminations.com