



# CC01

## Solar 12v / 24v Charge Controller

### TECHNICAL SPECIFICATIONS

#### GENERAL



- This programmable control module regulates and manages the solar panel power, battery power, and illumination timer.
- Pulse-width modulation (PWM) type charge controller.
- The compact control module has LED indicators to display status, input connections for solar panel and batteries and output connections for the lamp.
- Push button programming.
- Accepts and controls GEL and AGM sealed lead acid type (VRLA) batteries.
- Low voltage disconnect regulated by state of charge or voltage.
- Detects daytime and night time conditions via the solar panel.
- Automatic adaption to ambient temperature conditions.
- Safety features for short circuit and reverse polarity protection of battery and lamp inputs.
- Automatic voltage recognition.
- Float voltage for 12v system 13.7 or 24v system 27.4v dc.
- Low voltage disconnect for 12v system 11.4 ~ 11.9 or 24v system is 22.8 ~ 23.8v dc controlled by state of charge.
- Reconnect voltage for 12v system 12.5V or 24v system 25.6v dc.
- Dimensions approx. 11 cm x 10 cm x 4 cm (4" x 4" x 1.5") LxWxD.
- Ambient temperature range -40 deg C ~ +50 deg C (-40 deg F ~ +122 deg F).
- Programmable lock-out feature for optional use to prevent accidental or unauthorized tampering.
- User programmable illumination time of up to 1 to 12 hours or dusk-to-dawn setting (where conditions permit).
- Default setting is typically dusk to dawn.

**One Year\***  
Warranty ✓

**Low Price**  
Guarantee ✓

**No Hassle\***  
Returns ✓

**Worldwide**  
Shipping ✓

**Lifetime**  
Tech Support ✓

5611 Halifax Avenue • Fort Myers • FL • 33912 • USA • Phone: 239-461-5522 • Fax: 239-337-7887

MONDAY - FRIDAY 10.00AM - 4.00PM (US EASTERN TIME)

www.solarilluminations.com • sales@solarilluminations.com